

# Onyx

The thin vibrant veins of Onyx brighten any space and decorate the surfaces with the energy of stone. The natural elegance of this mineral is suitable for any type of coating. Its characteristic colours clad environments and bring out its best qualities.













Onyx

Onyx White




60x60 cm *Vitrified - Polished rect.*  
± 9,1 mm

Onyx Beige



60x60 cm *Vitrified - Polished rect.*  
± 9,1 mm

Onyx Grey



60x60 cm *Vitrified - Polished rect.*  
± 9,1 mm

Onyx White




60x60 cm *Vitrified - Satin rect.*  
± 9,1 mm

Onyx Beige



60x60 cm *Vitrified - Satin rect.*  
± 9,1 mm

Onyx Grey



60x60 cm *Vitrified - Satin rect.*  
± 9,1 mm



60x120 cm *Vitrified - Polished rect.*  
± 11 mm



60x120 cm *Vitrified - Polished rect.*  
± 11 mm



60x120 cm *Vitrified - Polished rect.*  
± 11 mm



60x120 cm *Vitrified - Satin rect.*  
± 11 mm



60x120 cm *Vitrified - Satin rect.*  
± 11 mm



60x120 cm *Vitrified - Satin rect.*  
± 11 mm



80x80 cm *Vitrified - Polished rect.*  
± 11,5 mm



80x80 cm *Vitrified - Polished rect.*  
± 11,5 mm



80x80 cm *Vitrified - Polished rect.*  
± 11,5 mm



80x80 cm *Vitrified - Satin rect.*  
± 11,5 mm



80x80 cm *Vitrified - Satin rect.*  
± 11,5 mm



80x80 cm *Vitrified - Satin rect.*  
± 11,5 mm

SHADE  
VARIATION



V3

WATER  
ABSORPTION



≤ 0,5 %

BREAKING  
STRENGTH (S)  
ISO 10545-4



≥ 1300 N

CHEMICAL  
RESISTANCE  
ISO 10545-13



GLA  
GHA  
(Resistant)

FROST  
RESISTANCE  
ISO 10545-12



Resistant

STAIN  
RESISTANCE  
ISO 10545-14



Class 5  
(Resistant)